



9532 Clear Premium Cast PVC Wrapping Film

Description

UNICAST 9532 Clear Premium Cast Wrapping Film is specially produced for lamination applications in conjunction with vehicle wrapping films. This Premium quality product provides a long service life for printed graphics and brings high performance with its Premium quality, high gloss, flexibility and even printability.

Area of Use

As an overlamine film for use with UNICAST 9520 Premium Cast Wrapping Film for long term vehicle wrapping applications requiring high quality performance, including applications over uneven and corrugated surfaces.

Release Liner

Specially produced highly stable 138g /sqm silicone coated kraft paper.

Adhesive

9532 Solvent based permanent clear adhesive

Printing

9532 films are suitable for printing machines which use solvent, eco solvent, UV and latex technology.

Teknik özellikler

Properties	Test Method	Value
Film Thickness	ISO 4591:1992	0,035 mm (35 micron)
Adhesive power	FINAT TM 1 (Stainless Steel)	Quick > 8 N/ 25 mm 20 minutes > 10 N/25 mm 24 Hours > 16 N/25 mm
Tensile Strength	ISO 527-1:2012	Along: >16 MPa Across: >16 MPa
Elongation Strength	ISO 527-1:2012	Along: >%120 Across: >%120
Dimensional Stability (150X150 mm / 48 hours /70	FINAT 14 / Steel	< 0,2 mm
Temperature Resistance		-30 °C ile +90 °C
Application Temperature		> +10 °C
Shelf Life		2 years (With original package at 23 C and 50% relative humidity)
Service Life		7 years

Attention

Before the application the surface must be cleaned from dust, powder, oil and all other things which will affect the adhesive properties. Freshly lacquered or painted surfaces must be kept waiting at least 2 weeks for maximum results. For all applications Unifol Application Guide must be considered. The statement in this data sheet is intended only as a source of information and is given without guarantee. For large application areas and wide range application differences, users must test the product for their applications.