







# ■ Model Specifications







Voltage:12V Unit Watts:1.5W Viewing Angel:150°

Modules/Chain:20 Chain/Pack:5

Model No.ColorW.L. (nm)Luminance (lm)LEDMG-W120Cool White10000K90





Voltage:12V Unit Watts:1.8W Viewing Angel:150°

Modules/Chain:20 Chain/Pack:1

Model No. Color W.L. Luminance (Im)
LEDML-W120C Cool White 10000K 125



Voltage:12V Unit Watts:9W Viewing Angel:150°

Modules/Chain:10 Chain/Pack:1

Model No. Color W.L. Luminance (Im)

LEDMD-W110C Cool White 10000K 550

Aluminum body with heat-conductive adhesive tape.

Using innovative, patent pending CooChip® technology, the LED chip is attached and bonded directly to the aluminum PCB and heat-sink, resulting in ultra low heat resistance. CooChip® Runs COOL!

Extended operating life at high ambient temperature, 75,000+ hrs@25°C / 50,000+ hrs@40°C


Power LED module designed for light box or big size channel letter illumination.


150° wide angle, emits much softer, more even light compared to regular LED Mmodule.

#### Applications


LED channel letter, light box.


### ■ Dimension Unit : mm













#### Radiation Characteristics

#### -/+180 Light intensity: Percentage -150 150 C0/180, 156.4° C30/210, 156.6° C60/240, 156.2° -120120 C90/270, 155.8° 0.0 -90 90 50% 75% -60 00% 30 -30 0 Average beam angle(50%): 156.2°

## Heat Management



# ■ Module Spacing Calculation in Light Box(Size:L\*M=1m\*1m)



D: Light box depth	S: Module spacing
--------------------	-------------------

D (inch)	2.5"	3"	4"	4.5"	5"
Smax. (inch)	5.5 <sub>ft</sub>	6.6 <sub>ft</sub>	6.6 <sub>ft</sub>	6.6 <sub>ft</sub>	6.6 <sub>ft</sub>
Quantity min.	42 <sub>pcs</sub>	30 <sub>pcs</sub>	30 <sub>pcs</sub>	30 <sub>pcs</sub>	30 <sub>pcs</sub>

D <sub>(mm)</sub>	60 <sub>mm</sub>	70 <sub>mm</sub>	80 <sub>mm</sub>	100 <sub>mm</sub>	120 <sub>mm</sub>
S <sub>max. (mm)</sub>	132 <sub>mm</sub>	154 <sub>mm</sub>	166 <sub>mm</sub>	166 <sub>mm</sub>	166 <sub>mm</sub>
Quantity min.	56 <sub>pcs</sub>	42 <sub>pcs</sub>	36 <sub>pcs</sub>	36 <sub>pcs</sub>	36 <sub>pcs</sub>