



## F102WB30 POLYETHYLENE FOAM TAPE (48KG/M3)

### DESCRIPTION

- Closed cell PE Foam, with a filmic release liner.
- Coated on both sides with a high quality pressure sensitive solvent acrylic adhesive

### APPLICATIONS

- Mirror Mounting
- Point of sales and display

### TECHNICAL VALUES

<u>Specification</u>	<u>Test Method</u>
Foam Thickness	2.0mm
Foam Density	48kg/m <sup>3</sup>
Foam Colour	White
Liner Colour	Blue filmic
180° Peel Adhesion To Stainless Steel	>19.52N/25mm (PSTC-1)
Initial Tack	<5 cm (PSTC-6)
Holding Power	>24 hours (PSTC-7) (1.0kg/2.5cm x 25cm)
Holding Power For Temp. Resit 60°C	>24 hours (PSTC-7) (0.5kg/2.5cm x 2.5cm)
Temperature Range	-10 -- +60°C
Dynamic Shear	>2 kgf/cm <sup>2</sup> (300mm/min) ASTM D1002

### **Remarks:**

1. The above data are tested under lab condition; the last standard is subject to the last confirmation between the seller and the buyer.
2. Tolerance: Weight and Thickness:  $\pm 5\%$ ; Width:  $\pm 3\text{mm}$ ; Length:  $\pm 0.5\%$ .
3. The products should be stored at room temperature and be kept away from wet and/or heat sources.
4. It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied must be clean, dry, and free of grease and oil.
5. The users should take test before application so as to ensure suitability for their special purpose and technique.